

MATERIAL SAFETY DATA SHEET

PRODUCT TRADE NAME: **RED LINE SHOCKPROOF™ GEAR OIL**

REVISION DATE: January 22, 1997

CHEMICAL NAME: Mixture

NFPA CODE: Health: 1 Fire: 1 Reactivity: 0

SECTION 1 - HAZARDOUS INGREDIENTS

Olefin Sulfide

This material does not contain any chemical listed as a carcinogen or potential carcinogen by OSHA, IARC Monographs, or National Toxicology program at a concentration > 0.1%.

SECTION 2 - FIRE AND EXPLOSION HAZARDS

FLASH POINT: 450°F (232°C)
UPPER FLAMMABLE LIMIT: Not Determined.
LOWER FLAMMABLE LIMIT: Not Determined.
EXTINGUISHING MEDIA: CO₂, dry chemical, foam.
SPECIAL FIREFIGHTING PROCEDURES: None
UNUSUAL FIRE & EXPLOSION HAZARDS: None

SECTION 3 - HEALTH HAZARD DATA

ORAL TOXICITY: LD 50 greater than 5000 mg/kg in rats. Based on data from components.
EYE IRRITATION: May cause mild eye irritation. Based on data from components.
SKIN IRRITATION: May cause mild skin irritation. Based on data from components.
OTHER: Unknown.
TLV: None established. Oil mist TLV 5mg/m³.

FIRST AID PROCEDURES

SKIN: Wash well with soap and water.
EYE: Flush well with water.
INHALATION: Remove to fresh air. See a physician if irritation persists.
ORAL: Call a physician. Drink copious water to induce vomiting.
ADDITIONAL: None.

SECTION 4 - SPECIAL PROTECTION INFORMATION

VENTILATION PROCEDURE: Mechanical ventilation recommended.
GLOVES PROTECTION: Neoprene or nitrile rubber gloves recommended.
EYE PROTECTION: Safety glasses.
OTHER PROTECTION: Long-sleeved shirt.

PRODUCT TRADE NAME: **RED LINE SHOCKPROOF™ GEAR OIL**
REVISION DATE: January 22, 1997

SECTION 5 - PHYSICAL DATA

VAPOR PRESSURE: Not Determined
SPECIFIC GRAVITY: 0.94 @ 15.6°C
WATER SOLUBILITY: Insoluble
PERCENT VOLATILE: Not Determined.
VAPOR DENSITY: Not Determined.
EVAPORATION RATE: Not Determined.
ODOR: Mild pungent odor.
APPEARANCE: Red opaque grease.

SECTION 6 - STABILITY

STABILITY: Stable
INCOMPATIBILITY: Oxidizing agents
POLYMERIZATION: Will not occur.
THERMAL DECOMPOSITION: Oxides of carbon, phosphorous, calcium, molybdenum, and sulfur.

SPILL OR LEAK PROCEDURES

SPILL PROCEDURES: Prevent entry into sewers and waterways. Pick up free liquid for disposal.
Absorb small amounts on inert material for disposal.

WASTE DISPOSAL: If disposed of, this material is expected to be a hazardous waste under RCRA due to toxicity. Disposal should be in compliance with federal, state, and local laws. If discarding this material, consider the possible relevance of the presence of the following chemicals and the treatment for the associated U.S. EPA RCRA Hazardous Waste Numbers: 0.00001% Benzene, CAS No:71-43-2, D018

SPECIAL PRECAUTIONS: Store in a cool, dry, place away from flame. Remove contaminated clothing and launder before reuse.

TRANSPORTATION AND LABELING

DOT PROPER SHIPPING NAME: Not Applicable.
DOT HAZARD CLASS: Not Applicable.
DOT ID NUMBER (UN NO.): None
EPA HAZARDOUS SUBSTANCES: None
U.S. TSCA INVENTORY: All components are included on the U.S. TSCA Inventory.

PRECAUTIONARY LABELS: None

The information presented herein has been compiled from sources considered dependable and is accurate to the best of Red Line's knowledge; however, Red Line makes no warranty whatsoever, expressed or implied, of merchantability or fitness for the particular purpose, regarding the accuracy of such data or the results to be obtained from the use thereof. Red Line assumes no responsibility for injury to recipient or to third persons or for any damage to any property and buyer assumes all such risks.