

Mobil 1 Synthetic Gear Lubricant 75W-90

Supreme Performance Synthetic Multi-Purpose Automotive Gear Lubricant

Product Description

Mobil 1 Synthetic Gear Lubricant is a supreme performance, synthetic, multi-purpose, SAE 75W-90 automotive gear lubricant designed to meet the highest level performance requirements of modern passenger vehicles in all types of operating conditions, as well as, deliver outstanding power transfer performance. Compared to conventional hypoid gear lubricants, Mobil 1 Synthetic Gear Lubricant 75W-90 performs exceptionally over a wide range of temperatures. Mobil 1 Synthetic Gear Lubricant 75W-90 achieves this through a unique proprietary formulation, that deliver optimised viscosity-temperature properties together with the highest level of inherent formulation stability and protects against thermal and oxidative degradation, wear and corrosion, viscosity loss associated with premature shearing. It also can be used in extended service and for aiding in fuel economy performance.

Mobil 1 Synthetic Gear Lubricant 75W-90 meets the most severe API Service MT-1 and GL-5 EP gear oil service classification.

Features & Benefits

Mobil 1 Synthetic Gear Lubricant 75W-90 combines wax-free synthesised hydrocarbon base oils and a specially designed extreme-pressure, limited-slip, sulphur-phosphorous additive system to provide a significantly higher level of performance in rear axles and differentials versus conventional fluids. Greater film strength at higher operating temperatures, reduced fluid friction and low-temperature application down to -50C provides significant advantages versus conventional mineral oil formulations. It reduces wear and spaulding under the high speed, high torque and high horsepower conditions in competitive racing and high performance automobiles. This unique, high technology final drive gear lubricant has demonstrated outstanding performance including; fuel economy, extended drain, long-term friction retention, low-temperature capability and improved differential/axle durability and cleanliness. Key features and benefits include:

| Features | Advantages and Potential Benefits |
|--|--|
| Exceptional thermal stability and resistance to high temperature oxidation | Extended gear and bearing life due to minimal deposits Longer seal life Potential extended oil drain/service intervals |
| Outstanding protection against low speed/high torque wear and against high speed scoring | Capability to handle the severest driving conditions while delivering smooth efficient and reliable performance |
| Exceptional shear stability | Retains viscosity and film strength under severe operating conditions to prevent wear |
| Excellent rust, staining and corrosion protection of copper and its alloys | Reduced wear Longer component life |
| Enhanced frictional properties | Improved fuel economy and reduced operating costs |

ExxonMobil Lubricants & Specialties

All products may not be available locally. For more information, contact your local sales office or visit www.exxonmobil.com.

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities. Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly.

© 2001 Exxon Mobil Corporation. All rights reserved.



| Features | Advantages and Potential Benefits |
|--|---|
| Outstanding low temperature fluidity versus mineral oils | Reduced wear at start up and ease of start up even in arctic conditions |
| Good resistance to foaming | Maintains film strength for reliable lubrication |
| Compatible with typical automotive seals and gaskets | Minimum leakage and reduced contamination |
| Excellent limited-slip performance | Reduced chatter and improved traction |

Applications

- Mobil 1 Synthetic Gear Lubricant 75W-90 is recommended for use in modern high performance automobiles like SUV's, Vans and Light duty trucks requiring API GL-5 & MT-1 level performance.
- Mobil 1 Synthetic gear Lubricant 75W-90 is intended for initial fill, topping-off or refilling differentials, final drives, transfer cases and other gear applications where lubricants meeting, API Service GL-5 and multi-purpose or mild EP gear lubricants are recommended.
- Mobil 1 Synthetic Gear Lubricant 75W-90 can also be used in rear axles where API Service GL-4 lubricant is recommended.
- Not recommended for automatic, manual or semiautomatic transmissions for which engine oil or automatic transmission fluids are recommended.
- Where extended service intervals and warranties are required.

Specifications & Approvals

| Mobil 1 Synthetic Gear Lubricant meets or exceeds the following industry specifications: | 75W-90 |
|--|--------|
| API GI-5/MT-1 | X |

Typical Properties

| Mobil 1 Synthetic Gear Lubricant | |
|----------------------------------|--------|
| SAE Grade | 75W-90 |
| Viscosity, ASTM D 445 | |
| cSt @ 40° C | 106 |
| cst @ 100° C | 15.2 |
| Viscosity Index, ASTM D 2270 | 150 |
| Pour Point, °C, ASTM D 97 | -46 |
| Flash Point, °C, ASTM D 92 | 175 |
| Density@15° C kg/l, ASTM D 4052 | A |

Health & Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design, Mobil 1 Gear Lubricant are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

ExxonMobil Lubricants & Specialties

All products may not be available locally. For more information, contact your local sales office or visit www.exxonmobil.com.

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities. Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly.

© 2001 Exxon Mobil Corporation. All rights reserved.

