



**Product**

**Type**

**MicroZol™ XP<sup>3</sup>**

**Synthetic Racing Oil**

**MicroZol™ XP<sup>3</sup> Synthetic Racing Oil Product Information:**

- For use in aluminum blocks and looser clearance race engines.
- Outstanding high temperature-high shear protection.
- Compatible with methanol and high octane race fuels.
- Recommended for:
  - Big Block dirt late model V-8 race engines
  - Sprint and midget race engines
  - Turbo and supercharged engines
  - Ideal for wet sump engines and other race engines with main and rod bearing clearances over 0.0025
- Uses advanced, proprietary lubricant technology exclusive to Joe Gibbs Performance.
- Viscosity typical of SAE 10W-30.

**Typical Physical Characteristics**

PARAMETER	TEST METHOD	VALUE
Pounds per U.S. gallon at 15.6°C	----	7.08
Specific Gravity at 15.6°C	ASTM D1298	0.850
Viscosity at 40°C, cSt	ASTM D445	70
Viscosity at 100°C, cSt	ASTM D445	12.0
Flash Point (PMCC), °C	ASTM D93	189
Pour Point, °C	ASTM D97	-54

\* MicroZol™ XP<sup>3</sup> can be blended and is completely compatible with MicroZol™ XP<sup>1</sup>, XP<sup>2</sup> and XP<sup>0</sup>.